

| XML Tag                             | Attributes | Parent Node            | Comments  | Value Required | I/O | Max Length* | Allowed Values  |
|-------------------------------------|------------|------------------------|---|----------------|-----|-------------|---|
| <b>&lt;StationConfiguration&gt;</b> |            |                        | Root node for the entire xml document   |                |     |             |   |
|                                     | count      |                        | Corresponds to the record count in the WL database table.   |                | 0   |             |   |
| <b>&lt;StationName&gt;</b>          |            | <StationConfiguration> | The Station Name is the name of the computer on the network   |                |     |             |   |
|                                     | id         |                        | Reserved for WorldLink  |                |     |             |   |
| <b>&lt;Sites&gt;</b>                |            | <StationConfiguration> |   |                |     |             |   |
|                                     | selected   |                        |   |                |     |             |   |
| <Site>                              |            | <Sites>                | Defines the Site that the Station Configuration belongs to. The record should exist in "Sites" table in the WorldLink database. |                |     |             |   |
|                                     | id         |                        | "Id" field  | Y              | I   |             |   |
| <PrinterTypes>                      |            | <StationConfiguration> |   |                |     |             |   |
| <PrinterType>                       |            | <PrinterTypes>         |   |                |     |             |   |
|                                     | id         |                        | Define the printer type identification  | Y              | I   |             | <b>0</b> -Eltron LPT<br><b>1</b> - DataMax<br><b>4</b> - SATO CL408<br><b>5</b> - Zebra A-300<br><b>6</b> - Zebra<br>105/140/5500 |
|                                     | Type       |                        | Define the Printer type "L" for the Label printer type  | Y              | I   |             |   |



| XML Tag     | Attributes | Parent Node            | Comments  | Value Required | I/O | Max Length* | Allowed Values   |
|-------------|------------|------------------------|---|----------------|-----|-------------|--|
| <ComPorts>  |            | <StationConfiguration> | Define the Comport.   |                |     |             | 1- COM 1<br>2-COM 2<br>3-COM 3<br>4-COM 4<br>5-COM 5<br>6-COM 6<br>7-COM 7   |
| <Port >     |            | <ComPorts>             | Define the port which is available on the machine                           |                |     |             |  |
|             | id         |                        | Defines the selected Comport id.  | Y              | I   |             |  |
| <BaudRates> |            | <StationConfiguration> | Defines the Communication with the ComPort.                                 |                |     |             | 0-110<br>1-300<br>2-1200<br>3-2400<br>4-4800<br>5-9600<br>6-19200<br>7-38400<br>8-57600<br>9-115200<br>10-230400<br>11-460800<br>12-921600 |
| <BaudRate>  |            | <BaudRates>            |   |                |     |             |  |
|             | id         |                        | Define the Baud rate communication with ComPort, which is selected by user. |                |     |             |  |
| <DataBits>  |            | <StationConfiguration> | Defines the Communication with the ComPort.                                 |                |     |             | 0-5<br>1-6<br>2-7<br>3-8   |
| <DataBit>   |            | <DataBits>             |   |                |     |             |  |
|             | id         |                        | Define the DataBit communication with ComPort which is selected by user.    |                |     |             |  |
| <Parities>  |            | <StationConfiguration> | Defines the Communication with the ComPort.                                 |                |     |             | 0-Even<br>1-Odd<br>2-None<br>3-Mark<br>4-Space   |
| <Parity>    |            | <Parities>             |   |                |     |             |  |



| XML Tag         | Attributes | Parent Node            | Comments  | Value Required | I/O | Max Length* | Allowed Values      |
|-----------------|------------|------------------------|---|----------------|-----|-------------|---------------------|
|                 | id         |                        | Define the Parity communication with ComPort which is selected by user. |                |     |             |                     |
| <StopBits>      |            | <StationConfiguration> | Defines the Communication with the ComPort.                             |                |     |             | 0-1<br>1-1.5<br>2-2 |
| <StopBit>       |            | <StopBits>             |   |                |     |             |                     |
|                 | id         |                        | Define the StopBit communication with ComPort which selected by user.   |                |     |             |                     |
| <LabelPrinter>  |            | <StationConfiguration> | Defines the Printing label.   |                |     |             |                     |
|                 | active     |                        | Reserved for WorldLink  |                |     |             |                     |
|                 | selected   |                        | Reserved for WorldLink  |                |     |             |                     |
|                 | mode       |                        | Reserved for WorldLink  |                |     |             |                     |
| <PrinterDriver> |            | <LabelPrinter>         | Define the label printing drive.  |                |     |             |                     |
| <FilePathName>  |            | <PrinterDriver>        |   |                |     |             |                     |
| <Port1>         |            | <StationConfiguration> |   |                |     |             |                     |
|                 | active     |                        | Defines the user selected Port.   |                |     |             |                     |
|                 | baudrate   |                        | Defines the user selected baudrate for communication with port.         |                |     |             |                     |
|                 | databits   |                        | Defines the user selected databit for communication with port.          |                |     |             |                     |
|                 | parity     |                        | Defines the user selected parity for communication with port.           |                |     |             |                     |
|                 | stopbits   |                        | Defines the user selected stopbit for communication with port.          |                |     |             |                     |
| <Port2>         |            | <StationConfiguration> |   |                |     |             |                     |
|                 | active     |                        | Defines the user selected baudrate for communication with port.         |                |     |             |                     |
|                 | baudrate   |                        | Defines the user selected databit for communication with port.          |                |     |             |                     |
|                 | databits   |                        | Defines the user selected parity for communication with port.           |                |     |             |                     |
|                 | parity     |                        | Defines the user selected stopbit for communication with port.          |                |     |             |                     |
|                 | stopbits   |                        |   |                |     |             |                     |
| <Port3>         |            | <StationConfiguration> |   |                |     |             |                     |
|                 | active     |                        | Defines the user selected baudrate for communication with port.         |                |     |             |                     |



| XML Tag  | Attributes | Parent Node            | Comments  | Value Required | I/O | Max Length* | Allowed Values         |
|----------|------------|------------------------|---|----------------|-----|-------------|------------------------|
|          | baudrate   |                        | Defines the user selected databit for communication with port.  |                |     |             |                        |
|          | databits   |                        | Defines the user selected parity for communication with port.   |                |     |             |                        |
|          | parity     |                        | Defines the user selected stopbit for communication with port.  |                |     |             |                        |
|          | stopbits   |                        |   |                |     |             |                        |
| <Port4>  |            | <StationConfiguration> |   |                |     |             |                        |
|          | active     |                        | Defines the user selected baudrate for communication with port. |                |     |             |                        |
|          | baudrate   |                        | Defines the user selected databit for communication with port.  |                |     |             |                        |
|          | databits   |                        | Defines the user selected parity for communication with port.   |                |     |             |                        |
|          | parity     |                        | Defines the user selected stopbit for communication with port.  |                |     |             |                        |
|          | stopbits   |                        |   |                |     |             |                        |
| <Port5>  |            | <StationConfiguration> |   |                |     |             |                        |
|          | active     |                        | Defines the user selected baudrate for communication with port. |                |     |             |                        |
|          | baudrate   |                        | Defines the user selected databit for communication with port.  |                |     |             |                        |
|          | databits   |                        | Defines the user selected parity for communication with port.   |                |     |             |                        |
|          | parity     |                        | Defines the user selected stopbit for communication with port.  |                |     |             |                        |
|          | stopbits   |                        |   |                |     |             |                        |
| <MOdule> |            | <StationConfiguration> | Define the selected modules number.                             |                |     |             |                        |
| <Error>  |            | <StationConfiguration> | Define the error message.                                       |                |     |             |                        |
|          | id         |                        |   |                |     |             | 0- No error<br>1-error |

