

XML Tag	Attributes	Parent Node	Comments	Value Required	I/O	Max Length*	Allowed Values
<Orgs>			Root node for the entire xml document				
	count		Corresponds to the record count in the WL database table.		0		
<Org>		<Orgs>	Contains the return header information				
	id		"Id" field in the "Organizations" table	Y	I		
	NodeIndex		Reserved for WorldLink	Y	I		0
<Xref>		<Org>	"CrossReference" field. It defines the organizations to be referenced in the WorldLink system.	Y	I	50	
<CompanyName>		<Org>	"CompanyName" field. It defines the organization name.	Y	I	50	
<Contact>		<Org>	"Contact" field. It defines point-of-contact for the organization.	Y	I	50	
<Address1>		<Org>	"Address1" field. It define the address of the organization.	Y	I	50	
<Address2>		<Org>	"Address2" field. It define the address of the organization.	Y	I	50	
<Address3>		<Org>	"Address3" field. It define the address of the organization.	Y	I	50	
<City>		<Org>	"City" field. It defines the city in which the organization resides.	Y	I	50	
<State>		<Org>	"State" field. It defines state in which the organization resides. This is a two-character abbreviation of the state name.	Y	I	10	
<Zip>		<Org>	"Zip" field. It defines the postal zip code of the organization.	Y	I	10	
<Country>		<Org>	"Country" field. It defines the country in which the organization resides.	Y	I	4	
<Email >		<Org>	"Email" field. It defines the email address of a point-of-contact for the organization.	Y	I	50	
<Phone>		<Org>	"Phone" field. It defines the phone number for the organization.	Y	I	20	
<Fax>		<Org>	"Fax" field. It defines the fax number for the organization.	Y	I	20	
<CI>		<Org>	"CI" field. It defines the Commercial Invoice.	Y	I	50	



Heightening Shipping Efficiency for World Commerce

Copyright © 2009 CMS GlobalSoft, Inc. All rights are reserved

Date Published: 3/26/2009 | Page 1 of 3

XML Tag	Attributes	Parent Node	Comments	Value Required	I/O	Max Length*	Allowed Values
<CICopies>		<Org>	"CICopies" field. It defines the value 1 or 0	Y			
<BOL >		<Org>	"BOL" field. It defines the Bill of Lading.	Y	I	50	
<BOLCopies>		<Org>	"BOLCopies" field. It defines the number of Copies	Y			
<EINNumber>		<Org>	"EINNumber" field. It defines the tax number of an organization is required.	Y	I	50	
<EINType>		<Org>	"EINType" field. It defines the tax type of the organizations.	Y			S-'Social Security' E-'EIN Number'
<AutoManifest>		<Org>	"AutoManifest" field. It defines the configuration of WorldLink to automatically open a manifest to enable shipping	Y			N.A.' 'Only Host Shipments' 'All Shipments'
<SED>		<Org>	"SED" field. It defines the SED report.	Y	I	50	
<SEDCopies>		<Org>	"SEDCopies" field. It defines the number of report copies.	Y			
<NAFTA>		<Org>	"NAFTA" field. It defines the NAFTA report.	Y	I	50	
<NAFTACopies>		<Org>	"NAFTACopies" field. It defines the number of report copies.	Y			
<CO>		<Org>	"CO" field. It defines the CO report.	Y	I	50	
<COCopies>		<Org>	"COCopies" field. It defines the number of report copies.	Y	I		
<SLI>		<Org>	"SLI" field. It defines the SLI report.	Y	I	50	
<DG>		<Org>	"DG" field. It defines the DG report.	Y	I	50	
<TNTDG>		<Org>	"TNTDG" field. It defines the TNTDG report.	Y	I	50	
<SLICopies>		<Org>	"SLICopies" field. It defines the number of report copies.	Y	I		
<DGCopies>		<Org>	"DGCopies" field. It defines the number of report copies.	Y	I		
<TNTDGCopies>		<Org>	"TNTDGCopies" field. It defines the number of report copies.	Y	I		



Heightening Shipping Efficiency for World Commerce

Copyright © 2009 CMS GlobalSoft, Inc. All rights are reserved

Date Published: 3/26/2009 | Page 2 of 3

XML Tag	Attributes	Parent Node	Comments	Value Required	I/O	Max Length*	Allowed Values
<UseAddVerification>		<Org>	"UseAddVerification" field. It defines the user address verification when shipping the package.	Y	I		
<AutoAddCorrect>		<Org>	"AutoAddCorrect" field. It defines the user address correction when shipping the package.	Y	I		
<IgnoreExceptions>		<Org>	"IgnoreExceptions" field. It defines for address verification Ignore exceptions.	Y	I		
<AutoSelectManifest>		<Org>	"AutoSelectManifest" field. It defines the auto select the manifest when shipping the package.	Y	I		
<DPV>		<Org>	"DPV" field. It defines Delivery point validation for the address verification.	Y	I		
<RDI>		<Org>	"RDI" field. It defines the Residential Delivery Indicator for address verification.	Y	I		
<USDF>		<Org>	"USDataFiles" field. It defines the US datafile for address verifications.	Y	I		
<UKDF>		<Org>	"UKDataFiles" field. It defines the UK datafile for address verifications.	Y	I		
<CanadaDF>		<Org>	"CanadaDataFiles" field. It defines the Canada datafile for address verifications.	Y	I		



Heightening Shipping Efficiency for World Commerce

Copyright © 2009 CMS GlobalSoft, Inc. All rights are reserved

Date Published: 3/26/2009 | Page 3 of 3