

XML Tag	Attributes	Parent Node	Comments	Value Required	I/O	Max Length*	Allowed Values
<Sites>			Root node for the entire xml document				
	count		Corresponds to the record count in the WL database table.		O		
<Site>		<Sites>	Contains the return header information				
	id		"Id" field in the "Site" table	Y	I		
	NodeIndex		Reserved for WorldLink	Y	I		0
<Xref>		<Site>	"CrossReference" field. It defines the code by which you want the site to be referenced in the WorldLink system.	Y	I	50	
<CompanyName>		<Site>	"CompanyName" field. It defines the name of the site.	Y	I	50	
<Contact>		<Site>	"Contact" field. It defines the point-of-contact for the site.	Y	I	50	
<Address1>		<Site>	"Address1" field. It defines the address of the site.	Y	I	50	
<Address2>		<Site>	"Address2" field. It defines the address of the site.	Y	I	50	
<Address3>		<Site>	"Address3" field. It defines the address of the site.	Y	I	50	
<City>		<Site>	"City" field. It defines the city in which the site resides.	Y	I	50	
<State>		<Site>	"State" field. It defines the state in which the site resides. This is a two-character abbreviation of the state name.	Y	I	10	
<Zip>		<Site>	"Zip" field. It defines the postal zip code of the site.	Y	I	10	
<Country>		<Site>	"Country" field. It defines the country in which the site resides.	Y	I	4	
<Email>		<Site>	"Email" field. It defines the email address of a point-of-contact for the site.	Y	I	50	
<Phone>		<Site>	"Phone" field. It defines the phone number for the site.	Y	I	20	
<Fax>		<Site>	"Fax" field. It defines the fax number for the site.	Y	I	20	
<GMTTime>		<Site>	"GMTTime" field. It defines the proper time zone.	Y	I	8	
<CurrencyCode>		<Site>	"CurrencyCode" field. It defines the currency code.	Y	I	3	

