

XML Tag	Attributes	Parent Node	Comments	Value Required	I/O	Max Length*	Allowed Values
<XRefGroups>			Root node for the entire xml document				
	count		Corresponds to the record count in the WL database table.		O		
<XRefGroup>		<XRefGroups>	Contains the return header information				
	id		"Id" field in the "XRefGroups" table	Y	I		
	NodeIndex		Reserved for WorldLink	Y	I		0
<Code>		<XRefGroup>	"Code" field. It defines the code by which you want the user group to be referenced in the WorldLink system.	Y	I	20	
<Description>		<XRefGroup>	"Description" field. It defines the description for the user group.	Y	I	100	
<GroupType>		<XRefGroup>	"GroupType" field. It defines the Org/Site groups marked with the user-group group type.				
<GroupValue>		<XRefGroup>	It defines the Org/Site group to be associated with the user group Code information.				
<UseCFC>		<XRefGroup>	"USECFC" field. It defines the Check for freight configurator.				
<UseCFCText>		<XRefGroup>			O		1- Yes 0 - No
<PromptBOL>		<XRefGroup>	"PromptBOL" field. It defines the Check the action for prompting BOL.				
<PromptBOLText>		<XRefGroup>			O		0-Merge Automatically 1- Prompt User For Action 2- Do Not Merge

